


# Product Specification



## CCFA-430

### Multiband Combiner

**Combines 700, 850, 1900 and AWS**

**High Band to Band Isolation**

**Low Loss Design**

---

## Electrical Specifications

### PASSBAND

700 + AWS BAND PORT

698 - 793 MHz, 1710 - 1755 & 2110 - 2155 MHz

850 + 1900 BAND PORT

824 - 894 MHz & 1850 - 2000 MHz

PASSBAND INSERTION LOSS

0.5 dB Max.

PASSBAND RETURN LOSS

20 dB Min.

PORT TO PORT ISOLATION

60 dB Min.

BAND TO BAND ISOLATION

60 dB Min.

PASSIVE INTERMODS

-153 dBc

POWER HANDLING

300 W CW / Avg.

5 kW Peak

Rev: 073119




# Product Specification

## Environmental Specifications

OPERATING TEMPERATURE	-50° to +60° Operating
ENVIRONMENTAL	Per ETS-300
WEATHERIZATION	Per IP-65 (IP-67 Optional)
LIGHTNING PROTECTION	Per EN / IEC 61000 4-5, Level 4

## Mechanical Specifications

CONNECTORS	7/16 DIN Female Optional: 4.3/10.0. Type 'N' Female
SIZE	9.98" x 7.98" x 3.0" Excluding Connectors
WEIGHT	Approx. 10 lbs.



### OUTLINE DRAWING

Rev: 073119