

Product Specification



CCFA-801-XDW

Multiband Combiner

- Covers Commonly Used AT&T Bands
- Use with FORCE™ Neutral Host Combiner
- Compact Size with Low Loss
- High Isolation / PIM Rated

Electrical Specifications

PASSBAND

COMMON PORT	698 - 2360 MHz
700 BAND PORT	698 - 787 MHz
850 BAND PORT	824 - 894 MHz
1900 BAND PORT	1850 - 1995 MHz
2100 BAND PORT	1695 - 1780 MHz & 2110 - 2180 MHz
2300 BAND PORT	2305 – 2360 MHz

INSERTION LOSS	0.8 dB Max, 0.5 dB Typ.
RETURN LOSS	20 dB Min.
ISOLATION	30 dB Min, 50 dB Typ.
POWER HANDLING	100W Avg. / 500 W Peak
PASSIVE INTERMODS	-156 dBc.

Environmental Specifications

OPERATING TEMPERATURE	-40° to +65°C Operating
ENVIRONMENTAL	IP-65 (Per IP-67 Optional)
ENVIRONMENTAL RATING	ETSI EN 300 019 Class 4.1, RoHS
LIGHTNING PROTECTION	EN / IEC 61000 4-5, Level 4
ALTITUDE	3,000m Max. (10,000 Ft)
MEAN TIME BETWEEN FAILURES	10 ⁷ Hrs. Min

Rev: 080219

Product Specification

Mechanical Specifications

CONNECTORS

4.3/10.0 Female


SIZE

8.6" [218.4] x 9.1" [231.1] x 2.9" [73.7mm]

Excluding Connectors

WEIGHT

Approx.: 10.7 lbs.



OUTLINE

Rev: 080219